



NBS Specification M50 (150)

Gerflor Taraflex Combisport Undercarriage System

A cradle and batten substructure, comprising of 40mm leg height Crumb Rubber Cradles, 43mm x 43mm Treated Kiln Dried Softwood Battens, 20mm x 150mm Foam Perimeter Strips and 2.40m x 0.60m x 18mm Tongued & Grooved Spruce Plywood; which when used in conjunction with Gerflor Sport M Plus playing surface provides a point and area elastic sports floor with a peak "g" deceleration of not more than 200g making the floor impact energy absorbing and area elastic in accordance with BS 7044 & BS EN 14904 Type C4.

The installation should be carried out in accordance with BS8203-2001, Subfloor to be smooth, hard, clean and dry prior to laying, where applicable the subfloor must incorporate a Damp Proof Membrane.

Flooring: Cradle & Batten Undercarriage System

Manufacturer and reference: Gerflor Ltd, Wedgnoek House, Wedgnoek Lane, Warwick, CV34 5AP
Tel 01926 401500, Fax 01926 401647.

Email: contractuk@gerflor.com

Reference: Gerflor Taraflex Combisport Undercarriage System

BS EN 685: Class Not applicable

Finished Floor Height 88mm-97mm (inclusive of the Sport M Plus playing surface)

Consult with Gerflor Ltd for any further requirements and for installation instructions.