



Gerflor Taraflex Combisport

Specification Details

System Components

- Taraflex Sport M Plus 7mm Top Layer
- 18mm Spruce T&G Plywood (2.4 x 0.6m Sheets)
- 43mm x 43mm Treated Kiln Dried Softwood Battens (1.8m Lengths)
- 40mm Leg Height Crumb Rubber Cradles (20mm thickness beneath batten not including packers)
- 1 x 5mm x 2 x 2mm Cradle Packers for levelling adjustment (additional packers to special order)
- 2 x 20mm x 150mm Foam Perimeter Strips (2m Lengths)
- 40mm x 7 Chipboard Screws (15 per sqm)
- PVA Adhesive (Approx 1 Litre per 36sqm)
- Final Finished Floor Height: 88mm – 97mm (123mm max with additional packers)

Pricing & Ordering

- Published Trade Price per sqm is based on a 640sqm (20m x 32m) hall i.e. a rectangular area with 104m of perimeter and allows for a 5% wastage factor. We therefore need only the dimensions of the hall to provide all the components required. For larger halls, small adjoining rooms or irregular shaped areas additional materials will be required, therefore the sqm price should be treated as a guide only, these additional components will require separate calculation and pricing.

Lead Times

- 4 – 5 Weeks Normally
- 4 – 6 Weeks June – Aug (Timber Mills Shutdown)