



NBS Specification M50 (150)

Mural Club

A homogeneous flexible vinyl sheet developed from a vinyl floorcovering which complies with EN 649. It is designed to be a permanent wall covering. Fully resistant to impacts, it acts as a buffer against damage from beds, trolleys and indoor motorised vehicles and other transportation systems. The joins are hot-welded to ensure perfect water-tightness.

Mural Club is available in 7 colourways

Installation should be carried out in accordance with BS8203-2001.

Consult with Gerflor Ltd for recommendations and requirements for adhesive fixing and seam welding.

Consult with Gerflor Ltd for technical details and to obtain samples.

Flooring roll: Vinyl

Manufacturer and reference: Gerflor Ltd, Wedgnoek House, Wedgnoek Lane, Warwick, CV34 5AP. Tel 01926 401500, Fax 01926 401647. Email: contractuk@gerflor.com

Reference: Mural Club

Width: 1500 mm

Thickness: 1.0 mm

Adhesive (and primer if recommended by manufacturer): Consult with Gerflor Technical Department for adhesive recommendations.

Seam welding: Consult with Gerflor Ltd for recommendations and requirements for seam welding.

Maintenance:

Mural Club is designed as a wall covering and therefore it is not necessary to use seals or polishes.

Post Installation Maintenance: The walls should be washed with a neutral cleaner in clean warm water. Rinsed with clean cold water and allowed to dry.

Regular/Periodic Maintenance: As above