



Taraflex Sport Performance Plus

A multipurpose floorcovering consisting of a top layer of PVC, a glassfibre mesh and a backing of bi-density PVC foam which gives a shock absorption of 41%.

Sport Performance Plus is available in 15 plain colourways and 2 wood designs.

Installation should be carried out in accordance with BS8203-2001. Subfloor to be smooth, hard, clean and dry prior to laying. Where applicable the subfloor must incorporate a Damp Proof Membrane. Consult with Gerflor Ltd for recommendations and requirements for adhesive fixing and seam welding.

Consult with Gerflor Ltd for technical details and to obtain samples.

Flooring roll: Multi layer sports vinyl

Manufacturer and reference: Gerflor Ltd, Wedgnoek House, Wedgnoek Lane, Warwick, CV34 5AP.

Tel 01926 401500, Fax 01926 401647.

Email: contractuk@gerflor.com

Reference: Taraflex Sport Performance Plus

BS EN 685: Class Not applicable

EN 660/1: Abrasion Resistance Not applicable

Width: 1500 mm

Thickness: 9.0 mm

Adhesive (and primer if recommended by manufacturer): Gerfix E120 Adhesive

Seam welding: Consult with Gerflor Ltd for recommendations and requirements for seam welding.

Maintenance:

Taraflex Sport Performance Plus comes with ProtecSol™ and has a Low Maintenance Classification.

No Emulsion Dressings are ever required.

Post Installation Maintenance: Sweep/Vacuum, Damp Mopping with Neutral Detergent

Regular Maintenance: Sweep/Vacuum, Damp Mopping with Neutral Detergent

Periodic Maintenance:

1. Spray Cleaning using a Rotary Polishing Machine with a Fine Pad