



NBS Specification M50 (150)

### **Taraflex Sport M Plus**

A multipurpose floorcovering consisting of a top layer of PVC, a glassfibre mesh and a dual density PVC foam backing which gives a shock absorption of 35%.

Sport M Plus is available in 15 different colourways and 2 wood designs.

Installation should be carried out in accordance with BS8203-2001, Subfloor to be smooth, hard, clean and dry prior to laying. Where applicable the subfloor must incorporate a Damp Proof Membrane. Consult with Gerflor Ltd for recommendations and requirements for adhesive fixing and seam welding.

Consult with Gerflor Ltd for technical details and to obtain samples.

**Flooring roll:** Multi layer sports vinyl

**Manufacturer and reference:** Gerflor Ltd, Wedgnoek House, Wedgnoek Lane, Warwick, CV34 5AP

Tel 01926 401500, Fax 01926 401647.

Email: [contractuk@gerflor.com](mailto:contractuk@gerflor.com)

**Reference:** Taraflex Sport M Plus

**BS EN 685: Class** Not applicable

**EN 660/1: Abrasion Resistance** Not applicable

**Width:** 1500 mm

**Thickness:** 7.0 mm

**Adhesive (and primer if recommended by manufacturer):** Gerfix E120 Adhesive

**Seam welding:** Consult with Gerflor Ltd for recommendations and requirements for seam welding.

**Maintenance:**

Taraflex Sport M Plus comes with ProtecSol™ and has a Low Maintenance Classification. No Emulsion Dressings are ever required.

**Post Installation Maintenance:** Sweep/Vacuum, Damp Mopping with Neutral Detergent

**Regular Maintenance:** Sweep/Vacuum, Damp Mopping with Neutral Detergent

**Periodic Maintenance:** Spray Cleaning using a Rotary Polishing Machine with a Fine Pad