



## **Sport Surface**

A multipurpose single layer floorcovering capable of withstanding storage units, the moving of machinery and public foot traffic.

Sport Surface is available in 9 different colourways.

Installation should be carried out in accordance with BS8203-2001. Subfloor to be smooth, hard, clean and dry prior to laying. Where applicable the subfloor must incorporate a Damp Proof Membrane. Consult with Gerflor Ltd for recommendations and requirements for adhesive fixing and seam welding.

Consult with Gerflor Ltd for technical details and to obtain samples.

**Flooring roll:** A single layer sport & multipurpose vinyl

**Manufacturer and reference:** Gerflor Ltd, Gerflor Ltd, Wedgnoek House, Wedgnoek Lane, Warwick, CV34 5AP. Tel 01926 401500, Fax 01926 401647.

Email: [contractuk@gerflor.com](mailto:contractuk@gerflor.com)

**Reference:** Taraflex Sport Surface

**BS EN 685: Class** Not applicable

**EN 660/1: Abrasion Resistance** Not applicable

**Width:** 1500 mm

**Thickness:** 2.1 mm

**Adhesive (and primer if recommended by manufacturer):** Gerfix E120 Adhesive

**Seam welding:** Consult with Gerflor Ltd for recommendations and requirements for seam welding.

### **Maintenance:**

**Sport Surface** comes with **Protecsol™** and has a **Low Maintenance Classification**. No Emulsion Dressings are ever required.

**Post Installation Maintenance:** Sweep/Vacuum, Damp Mopping with Neutral Detergent

**Regular Maintenance:** Sweep/Vacuum, Damp Mopping with Neutral Detergent

### **Periodic Maintenance:**

1. Spray Cleaning using a Rotary Polishing Machine with a Fine Pad