



**TARAFLEX SPORT M PLUS MAINTENANCE**

**Taraflex Sport M Plus contains ProtecSol® a patented UV cured heavy polyurethane treatment. No seals or polishes need ever be applied**

**Initial Maintenance**

After installation is completed the floor should be protected and left for 24 hours before any cleaning is carried out. The floor should then be:

1. Swept or vacuumed
2. Damp mopped or machine scrubbed with a neutral cleaner in clean warm water
3. Rinsed with clean cold water
4. Allowed to dry

**Routine & Periodic Maintenance**

As above

**Cleaning Hints**

If using a rotary cleaning machine do not use too coarse a pad as this can cause premature wear of games line marking.

Machine cleaning is best carried out using a machine with contra-rotating bristle brushes. Roto-Wash manufacture equipment that is particularly suited to Taraflex Sport. Contact:

Roto-Wash Tel: 0208 847 4545

Although most scuff marks will be removed by normal cleaning, stubborn marks can be safely removed using Perpetual Rubber Remover. Contact:

Perpetual Environmental Tel: 01252 395272

**Approved Maintenance Products**

Generic Description	Prochem	British Nova	Johnsons
	<b>0208 974 1515</b>	<b>01295 254030</b>	<b>0800 525 525</b>
<b>Neutral Cleaner</b>	Prodet	Liquid 99	Carefree Stride 1000

Many other maintenance products are available and may be used if they fit the generic description given above.

**Note: Manufacturers instructions regarding dilution rates, usage and rinsing must be strictly adhered to.**

**Protection**

No amount of maintenance will keep a floor looking good if measures are not taken to reduce the amount of dirt that is trafficked onto the floor. It is vital that adequate areas of suitable barrier mattings are used and that these mattings are themselves maintained correctly.

The following manufacturers can provide suitable products and advice.

Threshold Floorings Tel: 01793 764301

3M (UK) Plc Tel: 01344 484714

**Code of Practice**

BS 6263 Part 2 1991 Care and maintenance of floor surfaces. Code of practice for resilient sheet and tile flooring

Ink, Tomato, Mustard, Blood, Urine, Excrement	Diluted Bleach (Let it act without rubbing then rinse thoroughly)
Rust	Anti-rust or oxalic acid (rinse thoroughly)
Heavy grease, Paint, Rubber traces, Hair colour, Ball point or Felt pens	White Spirit

**Stain Removal**

**Warning**

Rubber can permanently stain PVC floorcoverings. Avoid using rubber backed mats, rubber furniture feet or rubber wheeled castors.