Mural Club

A homogeneous flexible vinyl sheet developed from a vinyl floorcovering which complies with EN 649. It is designed to be a permanent wall covering. Fully resistant to impacts, it acts as a buffer against damage from beds, trolleys and indoor motorised vehicles and other transportation systems.
The joins are hot-welded to ensure perfect water- tightness. Mural Club is available in 7 colourways
Installation should be carried out in accordance with BS8203-2001. Consult with Gerflor Ltd for recommendations and requirements for adhesive fixing and seam welding.
Consult with Gerflor Ltd for technical details and to obtain samples.

Flooring roll: Vinyl
Manufacturer and reference: Gerflor Ltd, Wedgnock House, Wedgnock Lane, Warwick, CV34 5AP. Tel 01926 622600, Fax 01926 401647. Email: contractuk@gerflor.com
Reference: Mural Club
Width: 1500 mm
Thickness: 1.0 mm
Adhesive (and primer if recommended by manufacturer): Consult with Gerflor Technical Department for adhesive recommendations.
Seam welding: Consult with Gerflor Ltd for recommendations and requirements for seam welding.
Maintenance:
Mural Club is designed as a wall covering and therefore it is not necessary to use seals or polishes.
Post Installation Maintenance: The walls should be washed with a neutral cleaner in clean warm water. Rinsed with clean cold water and allowed to dry.
Regular/Periodic Maintenance: As above