Taralay Element Compact

A multilayered vinyl floorcovering available in sheet form: The product comprises of a reinforced double glass fibre grid and printed design that is protected by a pure pvc wear layer with a Protecsol surface treatment for ease of maintenance.

Installation should be carried out in accordance with BS8203-2001, Subfloor to be smooth, hard, clean and dry prior to laying, where applicable the subfloor must incorporate a Damp Proof Membrane. Consult with Gerflor Ltd for recommendations and requirements for adhesive fixing and seam welding.

Consult with Gerflor Ltd for technical details and to obtain samples.

Flooring: Vinyl
Manufacturer and reference: Gerflor Ltd, Wedgnock House, Wedgnock Lane, Warwick, CV34 5AP. Tel: 01926 622600, Fax: 01926 401647
Email: contractuk@gerflor.com
Reference: Taralay Element Compact
Range: City
BS EN 685: Class 34 / 42
EN 660/2: Wear Resistance <2.0 mm
Slip Resistance: R10
Width: 2000 mm
Length: 25.00m
Thickness: 2.0 mm
Adhesive (and primer if recommended by manufacturer): Consult Gerflor Technical Department for further information
Seam welding: Joints should be hot welded using matching CR40 weld cord
Maintenance: No Emulsion Dressings are ever required
Post Installation Maintenance: Sweep/Vacuum, Damp Mopping with Neutral Detergent
Regular Maintenance: Sweep/Vacuum, Damp Mopping with Neutral Detergent
Periodic Maintenance:

1. Spray Cleaning using a Rotary Polishing Machine with a Fine Pad