

## **Creation 30 Mineral**

A Prestige decorative floor covering, multi layered construction comprising a compact flexible underlayer, a design interlayer and a clear treated wearlayer. The flooring complies with BS EN 649 with a Group T wear rating.

Creation 30 Mineral is available in a wide choice of mineral designs. It is suitable for use in all domestic locations and areas of low traffic use including hotels, nursing homes, offices etc.

Installation should be carried out in accordance with BS8203-2001, Subfloor to be smooth, hard, clean and dry prior to laying, where applicable the subfloor must incorporate a Damp Proof Membrane. Gerflor Ltd recommends the use of Gerfix E120 Adhesive. In areas such as conservatories where rapid temperature changes can occur the use of a proprietary High Temperature grade adhesive is necessary.

Consult with Gerflor Ltd for technical details and to obtain samples.

**Flooring:** Vinyl

**Manufacturer and reference:** Gerflor Ltd, Wedgnock House, Wedgnock Lane, Warwick, CV34 5AP. Tel: 01926 622600, Fax: 01926 401647

**Email:** [contractuk@gerflor.com](mailto:contractuk@gerflor.com)

**Reference:** Creation 30 Mineral

**BS EN 685:** Class 23 / 31

**EN 649/651:** Group T

**Tile Size:** 305 x 305 mm / 305 x 610 mm / 457 x 457 mm

**Thickness:** 2.5 mm

**Adhesive (and primer if recommended by manufacturer):** Gerflor E120

**Maintenance:** Creation 30 Mineral comes with a factory applied PUR+ (Polyurethane) coating and does not normally require an emulsion dressing and has a Low Maintenance Classification

**Post Installation Maintenance:**

1. Sweep/Vacuum, Damp Mopping with Neutral Detergent

**Regular Maintenance:** Sweep/Vacuum, Damp Mopping with Neutral Detergent

**Periodic Maintenance:**

1. Spray Cleaning using a Rotary Polishing Machine with a Medium Pad
2. Application of a proprietary Emulsion Dressing (Commencing 6-12 months after installation)
3. Strip & Reseal (when required)