

LAFITE CONNECT

gerflor.co.uk
gerflor.ie
gradus.com

Uniclass Pr_35_57_11_62
CI/SfB (43) Tn6

LAFITE CONNECT	
PLAINS, STRIPES, DESIGN	SPACE

SPECIFICATION

Product Format	Tile	Tile, Plank
Product Dimensions	500mm x 500mm	500mm x 500mm, 250mm x 1000mm
Product Construction	Tufted Loop Pile	Tufted Loop Pile
Surface Yarn	100% Aquafil Solution Dyed Nylon	Solution Dyed Nylon & Space Dyed Nylon
Total Carpet Weight	4415 g/m ²	4415 g/m ²
Tufted Pile Weight	540 g/m ²	540 g/m ²
Gauge	1/10" (39.4 per dm)	1/10" (39.4 per dm)
Stitches	43.3 per dm	43.3 per dm
Primary Backing	Non-woven	Non-woven
Secondary Backing	Bitumen	Bitumen
Total Carpet Thickness	5.9mm	5.9mm

PERFORMANCE SPECIFICATION

Classification BS EN 1307	Class 33	Class 33
Castor Chair BS EN 985 Test A	Pass	Pass
Static Electricity ISO 6356	<2kV	<2kV

FLAMMABILITY

BS EN 13501-1	Class Bfl-s1	Class Bfl-s1
---------------	--------------	--------------

WARRANTIES

Wear Warranty	10 Year	10 Year
Anti-static Warranty	10 Year	10 Year

ADHESIVES

For recommended adhesives contact Technical Services on 01625 428922



Environmental Profiles: Cert No. ENP 399
BRE Global (BREEAM): Lafite Connect achieves either A+ or A across all BREEAM defined building applications against which it has been assessed. For specific ratings visit: www.greenbooklive.com

AQUAFIL
synthetic fibres and polymers



IMPORTANT: The information contained in this document is valid from 01/07/2018 and is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force.

Contact us to order free samples

UNITED KINGDOM: Gerflor Ltd
Park Green, Macclesfield,
Cheshire, SK11 7LZ
Tel: 03332 412901
E-mail: contractuk@gerflor.com
Visit: www.gerflor.co.uk

IRELAND: Gerflor Ltd
Ballybay Road, Carrickmacross,
Co. Monaghan, Republic of Ireland
Tel: +353 (0) 42 966 1431
E-mail: gerflorirl@gerflor.com
Visit: www.gerflor.ie

Gerflor
theflooringroup