

Uniclass Pr_35_57_11_62
CI/SfB (43) Tn6

## LATOUR<sup>2</sup>

### SPECIFICATION

Product Format	Tile
Product Dimensions	500mm x 500mm
Product Construction	Tufted Loop Pile
Surface Yarn	100% Aquafil Solution Dyed Nylon
Total Carpet Weight	4320 g/m <sup>2</sup>
Tufted Pile Weight	470 g/m <sup>2</sup>
Gauge	1/10" (39.4 per dm)
Stitches	42.1 per dm
Primary Backing	Non-woven
Secondary Backing	Bitumen
Total Carpet Thickness	5.5mm

### PERFORMANCE SPECIFICATION

Classification BS EN 1307	Class 33
Castor Chair BS EN 985 Test A	Pass
Static Electricity ISO 6356	<2kV
Impact Noise Rating EN ISO 717-2, EN ISO 10140-3	22dB

### FLAMMABILITY

BS EN 13501-1	Class Bfl-s1
---------------	--------------

### WARRANTIES

Wear Warranty	10 Year
Anti-static Warranty	10 Year

### ADHESIVES

For recommended adhesives contact Technical Services on 01625 428922



Environmental Profiles: Cert No. ENP 399  
BRE Global (BREEAM): Latour<sup>2</sup> achieves either A+ or A across all BREEAM defined building applications against which it has been assessed. For specific ratings visit: [www.greenbooklive.com](http://www.greenbooklive.com)



IMPORTANT: The information contained in this document is valid from 01/02/2021 and is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force.

### Contact us to order free samples

**UNITED KINGDOM:** Gerflor Ltd  
Park Green, Macclesfield,  
Cheshire, SK11 7LZ  
Tel: 03332 412901  
E-mail: [contractuk@gerflor.com](mailto:contractuk@gerflor.com)  
Visit: [www.gerflor.co.uk](http://www.gerflor.co.uk)

**IRELAND:** Gerflor Ltd  
Ballybay Road, Carrickmacross,  
Co. Monaghan, Republic of Ireland  
Tel: +353 (0) 42 966 1431  
E-mail: [gerflorirl@gerflor.com](mailto:gerflorirl@gerflor.com)  
Visit: [www.gerflor.ie](http://www.gerflor.ie)