

IN STOCK
NOW

Nerok 70

High performance vinyl flooring for heavy traffic contract applications



Compact Sheet



Heavy Traffic



Ultra Realistic



Easy Maintenance

R10

Slip Resistant

PUR+

Surface Treatment

T

Wear Group

HETEROGENEOUS



0476 Noma Miel
LRV: 31.8




0492 Timber Cabana
LRV: 25.4




0669 Chene Light
LRV: 39.1



0720 Timber Clear
LRV: 41.2



1430 Oak Select Dark Grey
LRV: 30.7



1451 Noma Kola
LRV: 46.6



1518 Factory White
LRV: 46.2



1751 Timber Grey
LRV: 33.5



1893 Harbor Blue
LRV: 35.5




2012 Sherwood Clear
LRV: 38.1



2013 Sherwood Blond
LRV: 34.1



2015 Sherwood Brown
LRV: 18.7



2017 Sherwood Grey
LRV: 22.30



2242 Oak Select Country
LRV: 26.0



2244 Newport Clear
LRV: 43.0



2245 Newport Natural
LRV: 28.0

More colours plus acoustic version available - please contact us for details. **Check lead times upon order.**

LRV: Light Reflectance Value



Scan here
for matching
WELD RODS

Gerflor[®]

Nerok 70

Don't forget to order
your weld rods

High performance vinyl flooring for heavy traffic contract applications

PRODUCT DESCRIPTION	STANDARD	UNIT	NEROK 70
Total thickness	EN ISO 24346	mm	2.00
Wearlayer thickness	EN ISO 24340	mm	0.70
Weight	EN ISO 23997	g/m ²	2670
Width of sheet	EN ISO 24341	cm	200 / 400 ⁽¹⁾
Length of sheet	EN ISO 24341	lm	20
CLASSIFICATION			
Norm / Product Specification	-	-	EN ISO 10582
European classification	EN ISO 10874	class	34-43
Fire rating	EN 13501-1	class	B _{fl} -s1
Static electrical propensity	EN 1815	kV	< 2
Slip resistance wet	DIN 51130	class	R10
PERFORMANCES			
Wear resistance	EN 660.2	mm ³	≤ 2.0
Wear group	-	group	T
Type binder content	EN ISO 10582	type	I
Dimensional stability (norm)	EN ISO 23999	%	≤ 0.40
Residual indentation	EN ISO 24343-1	mm	≤ 0.10
Residual indentation (average measured value)	-	mm	≈ 0.05
Impact sound insulation	EN ISO 717-2	dB	≈ 6
Castor chair test (type W)	ISO 4918	-	OK
Thermal conductivity	EN ISO 10456	W/(m.k)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	PUR+
Chemical products resistance ⁽²⁾	EN ISO 26987	-	OK
ENVIRONMENT/INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/m ³	< 100
Certification	-	-	Floorscore®
CE MARKING			
	EN 14041		

⁽¹⁾ 2 metre width rolls are subject to stock availability. 4 metre width rolls available on order. Please contact us for lead times.

⁽²⁾ Regarding the resistance to chemicals, please download the corresponding leaflet from our website.



IMPORTANT: The information contained in this document is valid from 01/01/2024 and is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force. Rubber leaves indelible stains on vinyl floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyimide. Place mats of sufficient length at entrances to reduce outside sources of dirt.



Uniclass Pr_35_57_71_67		
Cl / Sfb	(43)	n6

UK reference - January 2024

we care / we act Our Commitments for a Sustainable future

CARBON FOOTPRINT*
-20% kg CO₂ equivalent/m² between 2020 and 2025

BIOSOURCED CONTENT**
10% by 2025

RECYCLED CONTENT
30% by 2025

ADHESIVE FREE***
35% by 2025

ANNUAL VOLUME RECYCLED
60,000 t by 2025

gerflor.co.uk | gerflor.ie

Gerflor®

*Scopes 1 & 2 defined in the GHG protocol **% of activity with biosourced materials ***% of activity with adhesive free solutions.