

STRATUS COLOUR ZONE

gerflor.co.uk
gerflor.ie
gradus.com

Uniclass Pr_35_57_11_62
CI/SfB (43) Tn6

STRATUS

SPECIFICATION

Product Format	Tile
Product Dimensions	500mm x 500mm
Product Construction	Tufted Cut Pile
Surface Yarn	ECONYL® Regenerated SDN
Total Carpet Weight	4585 g/m²
Tufted Pile Weight	615 g/m²
Gauge	1/10" (39.4 per dm)
Stitches	37.5 per dm
Primary Backing	Non-woven
Secondary Backing	Bitumen
Total Carpet Thickness	6.8mm

PERFORMANCE SPECIFICATION

Classification BS EN 1307	Wear Class 33
Castor Chair BS EN 985 Test A	Pass
Impact Noise Reduction ISO 10140-3	23dB
Static Electricity ISO 6356	<2kV

FLAMMABILITY

BS EN 13501-1	Class Bfl-s1
---------------	--------------

WARRANTIES

Wear Warranty	12 Year
Anti-static Warranty	10 Year

ADHESIVES

For recommended adhesives contact Technical Services on 01625 428922
--



Environmental Profiles: Cert No. ENP 399
BRE Global (BREEAM): Stratus, Emphasis & Stratus Stripe achieve either A+ or A across all BREEAM defined building applications against which they have been assessed. For specific ratings visit: www.greenbooklive.com



IMPORTANT: The information contained in this document is valid from 01/07/2018 and is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force.

Contact us to order free samples

UNITED KINGDOM: Gerflor Ltd
Park Green, Macclesfield,
Cheshire, SK11 7LZ
Tel: 03332 412901
E-mail: contractuk@gerflor.com
Visit: www.gerflor.co.uk

IRELAND: Gerflor Ltd
Ballybay Road, Carrickmacross,
Co. Monaghan, Republic of Ireland
Tel: +353 (0) 42 966 1431
E-mail: gerflorirl@gerflor.com
Visit: www.gerflor.ie

