

Taralay Impression

A unique, stunning and eco-friendly collection, designed just for you





Contents

03. Taralay Impression

The original & eco-designed range, created for you

04. A collection that serves its users

05. 2 technical solutions

06. Taralay Impression hop

Eco-design implemented at each stage of the life cycle

10. Design concepts

12. New designs and colours

28. Taralay Impression palette LRV/NCS Table

31. Gerflor & the DSDC approach

33. Technical data

Find out more gerflor.fr

Find us on social media:









Taralay Impression...

the original & eco-designed range, created for you

For multiple high traffic uses













Education

government

businesses

1 collection 4 solutions

Compact Version Easy wheeling & indentationresistant

Acoustic Version High-performance sound insulation

Glue-down installation

Taralay Impression

Taralay Impression Acoustic



Looselay



Taralay Impression

19 dB

Taralay Impression

Taralay Impression hop:

The easy solution for new-builds or renovation projects

... the answer to all your needs

A collection that serves its users

PROTECSOL® 2, THE STAIN GUARD


- Reduces cleaning time & saves money
- Uses less water and fewer cleaning products (detergent etc.)
- Resistant to chemicals




Its water-repellent effect prevents products that stain from penetrating.

Stains get ingrained in all other floor covering products on the market.

Stain test




Results after cleaning



Full stain resistance table available on request

REDUCED PUSH FORCE REQUIRED FOR WHEELING AROUND HEAVY LOADS

Comparison of Taralay Impression vs competitors*




2 technical solutions

Taralay Impression – Glue-down installation

Enhanced durability to withstand heavy traffic usage

Over 20 million m² of flooring have been installed since the 1st generation of Taralay Impression. Brand new designs and colours with all the usual long-standing benefits: sustainable, easy to clean and available in a wide range of designs.



- 1 Protecsol² extra-matt surface treatment
- 2 Transparent wear layer
- 3 Design
- 4 Fibreglass
- **5** Compact interlayer
- 6 High density foam (acoustic version)

Available in a compact 8 dB or an acoustic 19 dB version


Taralay Impression hop - Looselay



EXCLUSIVE PRODUCT CONSTRUCTION, ESPECIALLY DEVELOPED FOR LOOSELAY INSTALLATION!

A stable and expansion-resistant looselay flooring

The double fibreglass + glass laid scrim reinforcement ensures excellent product maintenance. The looselay layer that is made of **recycled materials** combined with a **technical underlay** improves the product's adhesion to the floor.



- 1 Protecsol² extra-matt surface treatment
- 2 Transparent wear layer
- 3 Design
- 4 Fibreglass
- 6 Compact interlayer
- 6 Glass fiber grid
- Calendered layer with recycled content
- 8 Technical underlay
- High density foam (acoustic version)
- hop holding tape

Available in a compact 8 dB or an acoustic 19 dB version

Eco-design valued at each stage of the life cycle

Taralay Impression

GERFLOR IS COMMITTED

to communicating transparently about the carbon impact of its products and focusing on eco-design, including the use of sustainable raw materials, the sustainability of its products and circular economy



The 4 stages of the life cycle



+ 15%

Recycled content



Phthalate-free*



REACH compliant



2 - Installation made easy in busy environments



Place the HOP holding tape where the rolls join Code: 059E/Packaging: 50 ml/box



Reinforced holding tape:

- Durable
- Easy to position
- No transfer to surface underneath



Unroll



Adhesive free: less disruption (smell, noise, dust) and fewer risks of quality issues



Ready to walk on straight away



Can be walked on immediately



In a renovation project **the preparation time is reduced** or unnecessary

^{*}Excluding recycled content



Eco-design valued at each stage of the life cycle





Protecsol²: stain resistant water-repellent surface saves water and detergent



Withstands wheeling heavy loads (straight or circular) up to 500 kg



Excellent resistance to indentation – 0.03 mm (compact)/ 0.08 mm (acoustic)



Excellent stability, even during temperature changes: expansion < 0.03%



Improved resistance to moisture



TVOC < 10 micrograms/m³



← A second life made easier

-50%

Removal time reduced by 50% in renovations, without damaging the surface underneath



Uninstall and reuse:

- Flooring can be uninstalled without damaging either the product or the surface underneath
- Flooring can be re-used for another building



Easy to recycle

- Qualifies for the **Second Life Programme**.
- Flooring is incorporated back into our production lines



A unique partnership with Paprec, recycling programmes that are certified by Eucertplast





Accelerating recycling is essential for building a more circular economy. Preserving resources and reducing the carbon footprint of our business are our commitments for Sustainable Development.



Taralay Impression

the original & eco-designed range, created for you

96 wood, mineral, textile effects and graphics that can be coordinated with and match our Taralay Premium, Tarastep, wall solutions, etc.

Taralay Impression Taralay Impression

Taralay Impression Taralay Premium







Taralay Impression



Taralay Impression

Taralay Impression Taralay Impression

Taralay Impression Taralay Premium



Taralay Impression Tarastep Pro



Design concepts...


Black & White Chic and retro

Happy Fun and educational Biophilia Inspired by nature
















The warmth and comfort of a design inspired by woven natural fibres in unassuming colours is a perfect match for soft and subtle vintage environments.

Wood Fusion



Vood Fusion Nature 110



Raintree







Raintree Grey 1076

Raintree Natural 1077



Habana 3D

Habana 3D Blossom






pana 3D Blossom 1100 Habana



Habana 3D Vinales 1070



Nature Oak







re Oak Dark 1056



Nature Oak Blond 105

Nature Oak Clear 1055



Rivau



Rivau Nature 1110



Terrazzo





Terrazzo Black & White 1058





Terrazzo Napoli 1060

Rough







Rough Beige 1028

Finesse





Finesse Nature 1064





Finesse Paille 1065

Finesse Poudre 1066



Pure Wool







Pure Wool Beige 1073





Pure Wool Taupe 10

Pure Wool Grey 1072



Envol






Envol Black White 1098



Jungle







Jungle Grey 1040

Jungle Green 1039




Jungle Copper 1038




23


Nido

Nido Teal/Uni Matt Teal









Chess





Chess Black & White 1041



25

Happy



Happy Road 0923 Scan scale: 10%






Happy Form 1101 Scan scale: 5%



Happy Number Blue 1102 Scan scale: 5%



Happy Number Grey 1103 Scan scale: 5%



Taralay Impression palette



Uni Matt Light Beige

Nest Metal



Uni Matt Yellow

Kubes Lemon

Codes	Colours	LRV	NCS	Taralay Impression hop
0540	O	20.5	4500 V	0
0543 0524	Cemento Brescia Cemento Capri	32,5 21,8	4502-Y 5010-Y30R	
1025	Cemento Firenze	22	5005-Y80R	0
0523 1024	Cemento Genova	43,1 33,8	3005-Y50R 4502-B	0
1024	Cemento Napoli Cemento Roma	33,8 37,8	3005-Y50R	0
1093	Charme Kraft	26,9	4010-Y30R	Ö
0723	Charme Pecan	24,3	5502-R	
1041	Chess Black & White	36,7	1002-Y50R + 8000-N	
1098	Envol Black & White	44,4	1002-R	
1099 1063	Envol Forest Finesse Brown	<u>48</u> 36	1505-Y90R 3010-Y50R	<u> </u>
1064	Finesse Nature	37,6	3502-Y	
1065	Finesse Paille	44,5	3020-Y	0
1066 1043	Finesse Poudre Flipkube Garden	40,5 18,6	3010-R10B 5030-G10Y	
1042	Flipkube Indigo	16,7	3050-R80B	
1044	Flipkube Lagoon	26,7	1565-B	
1075 1045	Flipkube Purple Flipkube White	16,2 42,7	4030-R60B 3005-Y80R	
1067	Gentlemen Black & White	34	3502-R	
0770	Gentlemen Clear	46,2	3002-R	<u> </u>
1068 1069	Gentlemen Denim Habana 3D Trinidad	23,2 24,7	4502-B 4010-Y50R	0
1070	Habana 3D Vinales	35,5	3010-Y40R	ő
1100	Habana 3D Blossom	35,1	3010-Y40R	
1101 1102	Happy Form Happy Number Blue	61,3 24,9	1502-G50Y 3040-R80B	
1103	Happy Number Grey	64,9	2500-N	
0923	Happy Road	56,9	1030-G50Y	
0720 0680	Infinity Aube Infinity Greige	47,9 33,1	3010-Y30R 4005-Y20R	0
1038	Jungle Copper	32,6	4010-Y50R	
1039	Jungle Green	23,6	4502-G	
1040 1046	Jungle Grey Kubes Anis	46,9 51,3	3000-N 1050-G60Y	
1031	Kubes Carmine	13,1	4040-R	
1027	Kubes Coral	30,4	2050-Y80R	
1030	Kubes Fuschia	20,2	2050-R20B	
1050 1047	Kubes Indigo Kubes Lemon	30 52,9	2040-R80B 1070-Y20R	
0755	Kubes White	64	1502-Y	
1048	Metallic Gold	43,1	3005-Y20R	
1049 0760	Metallic Silver Moon Island	49,2 24,8	3000-N 4010-Y30R	
1053	Nature Oak Blond	36,8	3005-Y50R	0
1054	Nature Oak Brown Nature Oak Clear	22,9 41,2	5010-Y30R	0
1055 1056	Nature Oak Dark	25,5	3005-Y20R 5005-Y20R	Ö
1051	Nest Blue	11,8	7010-R70B	
0745	Nest Metal	29,2	5500-N	0
1052 1062	Nest White Nido Beige	54,8 47,6	2502-R 2005-Y60R	
1036	Nido Brick	24,1	4020-Y70R	
1035	Nido Grey	62,1	1502-Y50R	
0519	Noma Beige	28,5	5010-R90B 5005-Y20R	
0373	Noma Ice	52	2002-Y50R	0
0773	Portobello Pura Waal Paiga	25,3	5005-Y20R	
1073 1072	Pure Wool Beige Pure Wool Grey	48,6 40	3005-Y50R 3005-R20B	
1071	Pure Wool Taupe	25	5005-Y80R	
1074	Pure Wool Teal	32,3	3502-R	
1076 1077	Raintree Grey Raintree Natural	24,5 31,4	5005-Y50R 5010-Y50R	0
0736	Rice Champagne	37,5	4010-Y30R	
0763	Rice Greige	48,5	3005-Y20R	
0737 1110	Rice Souris Rivau Nature	30,1 30	5000-N 4010-Y30R	0
1057	Riverside	13	6502-R	
1028	Rough Beige	37,8	3005-Y50R	<u> </u>
1029 0725	Rough Grey Sycamore Light Brown	34,2 25,6	4502-R 4010-Y30R	0
0727	Sycamore Vanilla	31,1	3020-Y20R	
1058	Terrazzo Black & White	68	1502-Y50R	
1059 1060	Terrazzo Brescia Terrazzo Napoli	52 63,7	2005-Y80R 1502-R	0
1090	Uni Matt Brick	23	4020-Y70R	**
1089	Uni Matt Copper	21,3	4030-Y50R	
1091 1088	Uni Matt Coral Uni Matt Dark Beige	28,4 36,8	2050-Y80R 3005-Y50R	0
1079	Uni Matt Dark Green	14,1	6005-B80G	
1080	Uni Matt Green	32,6	3030-G30Y	
0832 1078	Uni Matt Grey	43 34,1	3000-N 2030-R80B	0
1078 1084	Uni Matt Indigo Uni Matt Jungle Grey	29	4502-R	
1081	Uni Matt Lagoon	38,6	1050-B	
1092	Uni Matt Light Beige	48,2	2502-Y	0
1082 1083	Uni Matt Light Green Uni Matt Navy	46,9 9,1	3010-G30Y 7010-R70B	
1086	Uni Matt Powder	29,9	3020-R20B	
1085	Uni Matt Teal	17,7	5010-R90B	0
0848 1087	Uni Matt White Uni Matt Yellow	64,3 53,7	1505-Y20R 1060-Y10R	
1314	Walnut Brown	15,8	6020-Y40R	
1104	Wood Fusion Nature	28,1	4010-Y50R	0



Gerflor products help you to age well

These days, ageing well is a social challenge. In this context, supporting people who have dementia is the focus of numerous discussions.

What is dementia? Dementia is a syndrome that occurs in numerous neurological diseases (one of the most well-known being Alzheimer's disease), caused by progressive degeneration of certain neurons. These pathologies affect the memory, thoughts, behaviour and the ability to perform daily activities.

Gerflor is committed to helping towards ageing comfortably by developing designs and colours to suit these medical conditions.

BELOW ARE SOME KEY POINTS FOR CHOOSING A SUITABLE FLOORING:



Contrasting colours

Sections of the same area (floors, walls, accessories) must be in contrasting colours in order to improve the threedimensional perception of the different spaces and thus encourage movement. It is also important to take into account the light reflectance value (LRV*) of the different sections.

> All the LRVs in Gerflor ranges are available on our website and our communication tools.



'Soft' and almost plain patterns

Heavily patterned flooring or flooring with busy patterns should be avoided, as well as the colour black, which could lead to blocking reactions due to visual barriers. We therefore recommend choosing soft patterns.

> Many designs and colours in Gerflor's ranges have semi-plain or almost plain patterns that are perfectly suitable.



Matt flooring

In addition to the more realistic look, matt flooring is perceived as more secure. In fact, shiny floors can look wet, making people with dementia hesitant and increase the risk of falling.

> The latest-generation surface treatments developed by Gerflor (Protecsol® 2, Evercare™ in particular) give the products a matt appearance.



Acoustic comfort

You should opt for acoustic products that will reduce ambient noise and create a more calm and peaceful environment.

 Many of the Gerflor collections provide sound insulation. For example, Taralay Impression offers 19 dB (acoustic version) and 8 dB (compact version) sound insulation products.





Accredited products

Gerflor wanted to have its products (notably Taralay Impression) validated and accredited by the DSDC, **Dementia Services**

Development Centre.

This organisation is an independent and internationally recognised centre of knowledge and expertise dedicated to improving the lives of people with dementia.



Our customer feedback speaks volumes

'Taralay Impression is a high quality product that is very easy to maintain; The range we chose gave us the hotel style we were looking for.'

Belley Hospital

'The product was installed over 10 years ago. The floor covering withstands traffic really well. On top of that, just plain water gives a perfect clean.'

Rochefort Hospital

'I really liked the collection, in terms of aesthetics, and everybody else likes it. Also, the flooring is easy to clean and is stain-resistant.'

City of Mulhouse

'It's easy to wheel around heavy loads on Taralay Impression. It is also extremely hard wearing.'

Mulhouse & South Alsace Region Hospital Group

Technical data

			Taralay Impression Acoustic	Taralay Impression Compact	Taralay Impression hop Acoustic	Taralay Impression hop Compact
Description						
	EN ISO 24346	mm	3.35	2.00	4.35	2.30
Total thickness	ASTM F386-02	inch	0.13"	0.08"	0.17"	0.09"
Third and a formation of	EN ISO 24340	mm	0.65	0.70	0.70	0.70
Thickness of wearlayer	ASTM F410-02	inch	0.026"	0.028"	0.028"	0.028"
Mainh	EN ISO 23997	g/m²	2825	2635	3670	3200
Weight	-	lbs/sq.ft	6.23	5.81	8.09	7.05
Width/langth of shoot	EN ISO 24341	cm / Im	200 / 25	200 / 25	200 / 20	200 / 20
Width/length of sheet	-	feet - inch	6'6" / 82'	6'6" / 82'	6'6" / 65'7"	6'6" / 65'7"
Classification						
Norm/product specification	-	-	EN ISO 11638	EN ISO 10582	EN ISO 11638	EN ISO 10582
European classification	EN ISO 10874	class	34 - 42	34 - 43	34 - 42	34 - 43
Fire rating	EN 13501-1	class	B _{fl} -s1	B _{fl} -s1	B _{fl} -s1	B _{fl} -s1
Static electrical propensity	EN 1815	kV	< 2	< 2	< 2	< 2
Slip resistance wet: ramp test with oil	EN 16165 app B	classe	R10	R10	R10	R10
Performances						
Wear resistance	EN 660.2	mm³	≤ 2.0	≤ 2.0	≤ 2.0	≤ 2.0
Wear group	QB 30	group	T	T	T	Т
Type binder content	EN ISO 10582	type	-	1	1	I
Dimensional stability (requirement)	EN ISO 23999	%	≤ 0.40	≤ 0.40	≤ 0.40	≤ 0.40
Dimensional stability (measured value)	-	%	0,08	0,08	0,03	0,03
Residual indentation (requirement)	EN ISO 24343-1	mm	≤ 0.20	≤ 0.10	≤ 0.20	≤ 0.10
Residual indentation (average measured value)	-	mm	≈ 0.08	≈ 0.03	≈ 0.08	≈ 0.03
Impact sound insulation	EN ISO 717-2	dB	19	8	19	8
Castor chair test (type H)	ISO 4918	-	OK	OK	OK	OK
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25	0.25	0.25	0.25
Colour fastness	EN 20 105 - BO2	degree	≥ 6	≥ 6	≥ 6	≥ 6
Surface treatment	-	-	PROTECSOL® 2	PROTECSOL® 2	PROTECSOL® 2	PROTECSOL® 2
Chemical products resistance (1)	EN ISO 26987	-	OK	OK	OK	OK
Anti-bacterial activity (E. coli - S. aureus - MRSA) (2)	ISO 22196	-	> 99% inhibits growth	> 99% inhibits growth	> 99% inhibits growth	> 99% inhibits growth
Antiviral activity (human coronavirus) after 2h ⁽²⁾	ISO 21702	-	> 99.7 % virucidal activity	> 99.7 % virucidal activity	> 99.7 % virucidal activity	> 99.7 % virucidal activity
Environment / Indoor Quality Air						
TVOC after 28 days	ISO 16000-6	microgram/m ³	< 10	< 10	< 10	< 10
• -			Floorscore®	Floorscore®	Floorscore®	Floorscore®

((



(1) Regarding the resistance to chemicals, please download the corresponding

leaflet from our website.

(2) The implementation of an effective cleaning regime is the most important

Product description and technical data sheets on gerflor.com

Installation and Maintenance Guidelines, Complementary ranges available on our

Rubber leaves indelible stains on vinyl floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside

IMPORTANT: The information contained in this document is valid from 01/03/2023 and is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force.



We care / We act Our Commitments for a Sustainable future



CARBON FOOTPRINT* -20 % kg CO₂ equivalent/m² between 2020 and 2025



BIOSOURCED CONTENT** 10 % by 2025



RECYCLED CONTENT **30 %** by **2025**



ADHESIVE FREE" 35 % by 2025



