

## **Taraflex™ Sport M Evolution**

A sports floor covering consisting of a top layer of PVC, a glass fibre mesh and dual density PVC foam backing. Combined, this results in European Norm 14904 classification of **P1** for shock absorption.

Taraflex™ Sport M Evolution is available in 17 different colours and 2 wood designs. Installation should be carried out in accordance with BS8203-2001, sub floor to be clean, smooth, flat, sound and permanently dry prior to laying, where applicable the sub floor must incorporate a Damp Proof Membrane. Consult with Gerflor Ltd for recommendations and requirements for adhesive fixing and seam welding.

Consult with Gerflor Ltd for technical details and to obtain samples.

**Flooring:** Multi Layer Sports Vinyl

**Manufacturer and reference:** Gerflor Ltd, Wedgnock House, Wedgnock Lane, Warwick, CV34 5AP. Tel: 01926 622600, Fax: 01926 401647

**Email:** [contractuk@gerflor.com](mailto:contractuk@gerflor.com)

**Reference:** Taraflex™ Sport M Evolution

**BS EN 685:** Not applicable

**EN 660/1:** Abrasion Resistance Not applicable

**Width:** 1500 mm

**Thickness:** 7.0 mm

**Adhesive (and primer if recommended by manufacturer):** Gerfix E120 Adhesive

**Seam welding:** Consult with Gerflor Ltd for recommendations and requirements for seam welding.

**Maintenance:** Taraflex™ Sport M Evolution comes with ProtecSol® and has a Low Maintenance Classification. No Emulsion Dressings are ever required

**Post Installation Maintenance:** Sweep/Vacuum, Damp Mopping with Neutral Detergent

**Regular Maintenance:** Sweep/Vacuum, Damp Mopping with Neutral Detergent

**Periodic Maintenance:**

1. Spray Cleaning using a Rotary Polishing Machine with a Fine Pad